

## Products

SC VF 28.8.ADR

Desktop 28.8

SC V.34 DBU

SC 553

SC 5001

SC 800T3

SCIP

SCIP-MR1

Line Type	Format	Managed	Security	DTE	Benefit
PL/SN	S/R	■	1 Opt. 2,3,4	1 2,3 Optional	2/4 Wire Private Line with Dial Restoral. Robust Security.
PL/SN	S		1 Opt. 2,3,4	1	2/4 Wire Private Line with Dial Restoral. Robust Security.
PL/SN	S/R	■	1	1	Dial Restoral for DDS, Mux channel etc.
T1	S/R	■		2 3 Optional	Fault Tolerant Redundant Hardware and Circuit Diversity
T1	R	■		Optional * 1,2,3	Safe T1 with Redundant Hardware and Circuit Diversity
T3	S/R	■		HSSI	Diverse Routing with SONET Ring
T1	S/R	■	5	Ethernet Switch	Safe LAN-X Transparent Ethernet Modem with Redundant Hardware and Circuit Diversity
T1	S/R	■	5,6	Ethernet Switch	Robust Mini-Router (RIP, OSPF) with VRRP and Security Features (SSH, MD5)

PL = Private Line  
SN = Switched Network/Dial Up  
DDS = Digital Data Service  
\* = via SC 5520, SC 5553 or SC 5034

T1 = 1.544 Mbps Service  
T3 = 45 Mbps Service  
S = Standalone  
R = Rackmount

Security: 1 = Steadfast, Callback & Password  
2 = AES Encryption  
3 = Radius  
4 = Secure Access Control  
5 = Multi-Level Password, TACACS+  
6 = MD5, SSH

DTE 1 = RS232  
DTE 2 = V.35  
DTE 3 = RS530  
DTE 4 = DSX1

SC 5000 High Density Shelf



SC 2000 Shelf



DataComm High Density Shelf  
With SpectraComm Blade Adapter



SC1001 / 1002 Enclosure



Desktop Enclosure

